


General Purpose Plastic Rectifiers

PRODUCT SUMMARY

Reverse Voltage 50 to 1000 Volts
 Forward Current 6.0 Amperes




R-6 or P600

FEATURES

- Low forward voltage drop
- High current capability
- High reliability
- High surge current capability
- T_J is 150°C (Max.) and T_{STG} is 175°C (Max.) with PI glue

MECHANICAL DATA

- Cases: Molded plastic R-6
- Epoxy: UL 94V-O rate flame retardant
- Lead: Axial leads, solderable per MIL-STD-202, Method 208 guaranteed
- Polarity: Color band denotes cathode end
- High temperature soldering guaranteed:
 250°C/10 seconds .375" (9.5mm) lead lengths at 5 lbs., (2.3kg) tension
- Weight: 0.074 ounce, 2.1 grams



Dimensions in inches and (millimeters)



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

Parameter	Symbols	6A05	6A1	6A2	6A4	6A6	6A8	6A10	Units
Maximum repetitive peak reverse voltage	V_{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	560	700	Volts
Maximum DC blocking voltage	V_{DC}	50	100	200	400	600	800	1000	Volts
Maximum average forward rectified current 0.375" (9.5mm) lead length @ $T_A=60^\circ\text{C}$	$I_{(AV)}$	6.0							Amps
Peak forward surge current, 8.3 ms single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	400.0							Amps
Maximum instantaneous forward voltage @ 6.0A	V_F	0.95							Volts
Maximum DC reverse current @ $T_A=25^\circ\text{C}$ at rated DC blocking voltage @ $T_A=100^\circ\text{C}$	I_R	10.0 400							μA
Maximum full load reverse current full cycle average, .375" (9.5mm) lead length @ $T_A=75^\circ\text{C}$	$I_{R(AV)}$	50							μA
Typical junction capacitance (Note 1)	C_J	100							pF
Typical thermal resistance (Note 2)	R_{JA}	10.0							$^\circ\text{C/W}$
Operating junction temperature range	T_J	-55 to +125							$^\circ\text{C}$
Storage temperature range	T_{STG}	-55 to +150							$^\circ\text{C}$

- Notes:**
1. Measured at 1 MHz and Applied Reverse Voltage of 4.0 V D.C.
 2. Thermal Resistance from Junction to Ambient .375" (9.5mm) Lead Length

RATINGS AND CHARACTERISTIC CURVES

($T_A=25^{\circ}\text{C}$ unless otherwise noted)




FIG.2- TYPICAL FORWARD CHARACTERISTICS




FIG.3- TYPICAL REVERSE CHARACTERISTICS




FIG.4- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT





FIG.5- TYPICAL JUNCTION CAPACITANCE



Information furnished by Silicon Standard Corporation is believed to be accurate and reliable. However, Silicon Standard Corporation makes no guarantee or warranty, expressed or implied, as to the reliability, accuracy, timeliness or completeness of such information and assumes no responsibility for its use, or for infringement of any patent or other intellectual property rights of third parties that may result from its use. Silicon Standard reserves the right to make changes as it deems necessary to any products described herein for any reason, including without limitation enhancement in reliability, functionality or design. No license is granted, whether expressly or by implication, in relation to the use of any products described herein or to the use of any information provided herein, under any patent or other intellectual property rights of Silicon Standard Corporation or any third parties.